



# TRIME

Lighting Tower Specialist



# X-MESSAGE

## HYBRID

WITH LED PANEL

# X-MESSAGE

## HYBRID

WITH LED PANEL



820 Kg



200(l) - 0,5(l/h)



2 battery

- Led screen with hydraulic lifting system
- Very compact dimensions for easy handling & transportability, up to 16 units per truck
- Central lifting eye longitudinal and transversal forklift pockets for effective handling
- Control panel alarms for engine protection and fuel level indicator
- External emergency stop button
- Fully bunded tank, 110%
- 4 Extendable & height adjustable stabilizers



**16 Units per truck**

### TECHNICAL SPECIFICATIONS

General	
Dimensions min. (mm)	1100x1600x1980
Dimensions max. (mm)	2300x1600x2480
Total weight without fuel	820 Kg
Engine battery	12 V - 38 Ah
Fuel tank capacity	200 l
Running time before refill	726 h
Features	
Controller	DSE 3110
Battery charger	(230V 1Ph Built-in)
Emergency stop button	
Tilting lifting eye	
Engine	
Type	Yanmar L70AE
Number of cylinders	1
Displacement	320 cm <sup>3</sup>
Engine speed	3000 rpm
Fuel consumption	0,5 l/h
Cooling system	air

Batteries	
Type	AGM 12 V 160 Ah
Batteries number	2
Batteries pack	24Vdc
Expected battery cycle	500
Expected battery life time	9500h

Hybrid mode	
Running time	9 h
Charging time with LED panel off	± 10 h
Complete discharge / charge cycle	19 h
Hybrid mode consumption	0,26 l/h

LED Screen	
Dimensions (mm)	1100x1900
Definition(Pixel)	10/mm <sup>2</sup>
Frequency(Hz)	1920
Screen Operating temperature	-20°/+55°
Supply	220V

