INDUSTRIAL LINE



Code	IP200-120TS0		
Mechanical version	steel she canopy, c	version with galvanized et and powder-painted ompact base frame, with ank and leak control	
Fuel Tank Capacity	lt.	160	
Rated technical data			
Prime Power (PRP)	kVA	124	
Prime Power (PRP)	KW	99,2	
Limited Power (LTP)	kVA	135	
Limited Power (LTP)	KW	108	
Rated Power Factor (cosф)		0.8	
Windings		Three phases Series Star	
Rated three-phase concatenated Voltage	V	400	
Rated phase-neutral voltage	V	230	
Rated frequency	Hz	50	
Fuel type		Diesel	
Dimensions And Noise			
Length	mm	2560	
Width	mm	1040	
Height	mm	1805	
Weight	Kg	1690	
Sound pressure 7 m.	dBA	68	
Fuel consumption			
Fuel Cons. at 100% (LTP)	l/h	30,4	
Fuel Cons. at 100% (PRP)	l/h	27,6	
Fuel Cons. at 75% (PRP)	l/h	20,4	
Fuel Cons. at 50% (PRP)	l/h	14,4	
General Alternator Data			
Alternator brand		STAMFORD	
Alternator model		UCI274E	
PRP Power	kVA	140	
LTP Power	kVA	150	
Winding		Three phases Series Star	
Terminals Number		12 nr	
IP Protection		23	
Electronic regulator		AS440	
Precision		±1%	

The images of the products are indicative for illustrative purposes only.



General Engine Data			
Engine brand			FPT IVECO
Engine model			N45TM3
Cylinders			4
R.P.M.			1500
Cubic capacity			4500
Air intake			Turbo
Standard voltage		Vdc	12
Sae			3 - 11
BMEP		kPa	1937
Cooling			Water
Flywheel P.R.P. Power		kW	107,2
Flywheel Stand-by Power		kW	118,2
Electronic regulator			On request
Precision class			G2
Oil quantity		lt.	12,8
EU Stage	Ν	on emis	ssion certified
Standard Features			

Hard wires connection protected

Electrical panel ComAp AMF25 mounted on board with safety cover Circuit breaker

Internal exhaust gas silencer and insulated manifold Engine oil extraction pump and fuel decanter filter

12V Battery with battery switch

Bunded tank

Lifting hooks and side forklift pockets

Options *factory installed*

	220V Electric pre-heater			
	KIT socket TPS01:	1x32A, 1x16A 3Ph 1x16A 1Ph + 1x16A Schuko		
	KIT socket TPS03:	1x63A, 1x32A, 1x16A 3Ph 1x16A 1Ph + 1x16A Schuko 125A breaker with adj. earth fault relay		
	Kit AMF and ATS panel			
	Predisposition for quick release fitting for external fuel tank			

Oversize fuel tank 800 lt.



27030 Villanova D'Ardenghi (PV) Italy • Via Roma 6 Tel. +39 02 942 1464 • Sales Dept. +39 0382 406 252

www.trime.it info@trime.it

MGTP 120 SS FI