

**STAGE 5**  
**CERTIFIED**



## S-EVENT 20

Code **RP46-20MS4**

### RATED TECHNICAL DATA

Prime Power (PRP)	kVA	20
Prime Power (PRP) (cos φ)	kW	16
Limited Power (LTP)	kVA	21
Limited Power (LTP) (cos φ)	kW	16,8

### GENERATOR

Type	Linz Pro 18S/4
Power	20 kVA 400V
Frequency	Hz 50
CosD	0.8
Insulation class	H
Mechanical protection	IP23

### ENGINE

Engine brand	YANMAR
Engine model	4TNV88
N° cylinders	4
Displacement	cm <sup>3</sup> 2190
Power	HP 29,5
Engine speed	rpm 1500
Speed regulation	Mechanical
Cooling	Water
Fuel	Diesel
Starting system	Electric

### DIMENSIONS & WEIGHT

Noise level (dBA at 7mt)	55
Battery	V 12
Fuel tank capacity	lt 300
Length	mm 2150
Width	mm 974
Height	mm 1645
Dry weight	Kg 1250

The company reserves the right to modify the technical specifications, items and design without notice. The images of the products are indicative for illustrative purposes only.

### DISTRIBUTION PANEL:

- 1x 32A 1Ph 230V EEC socket
- 2x 63A 1Ph 230V EEC socket
- 2x 16A 1Ph 230V EEC socket
- 400V 3Ph hard wires prtected by safety switch

### STANDARD FEATURES:

- Super silenced canopy Lwa
- Super silenced exhaust gas silencer
- Built in fuel tank
- Bunded tank
- 12v battery
- Battery switch
- Forklift pocket
- Central lifting eye
- Heavy bump stoppers
- 3 ways valve for external fuel tank connection
- Gateway with external antenna

### ON BOARD CONTROL PANEL EQUIPPED WITH:

- DSE 7310
- ON/OFF switch
- Safety cover for DSE 7310 and circuit breakers
- Circuit breaker
- Earth leakage circuit breaker
- Remote start/stop connector
- Emergency stop

### OPTIONS

- Site tow trailer
- Road tow trailer