designed and created for your needs

power and innovation





6,5h recharging time

Designed to provide an exceptional level of performance for every work on site ensuring the right balance between power and ease of use

STATION

T-ZEROPRO

12 Charger points with key and numerical code



more sustainable and environmentally friendly future



solar hybrid

T-ZEROPRO





APPLICATIONS



Power for your tools

FEATURES

- Automatic battery switch
- Sound proof canopy
- Emergency stop
- Exhaust gas silencer
- Built in fuel tank
- Bunded tank
- Forklift pocket
- Heavy bump stoppers



battery pack inside

4 complete FULL cycles of charging

- Above calculations has been based on standard Average tools specs:
- Lithium battery 4Ah
- Battery Charger 80W consumption

power and innovation



imensions	
xWxH(mm)	2202x1133x2534
Weight (Kg)	1364
Fechnical data	
nlet plug	32A-230V
nverter	1x48V/3000VA
Continuous Inverter Output Power	3000VA
Recharging time	6.5h
Alternator	
1odel	Meccalte
Rated output (kVA)	6
Frequency (Hz)	50
/oltage(V)	230
nsulation class	Н
Degree of Protection	IP23
Engine	
Model	Kohler ISLD440
- uel	Diesel
Engine speed	3000 rpm
loise level at 7mt	65dBA
missions regulations	stage V
onsumption only engine mode	
Tank capacity	2501
uel consuption - Running time	1,4 I/h-180 hrs
atteries	
attery	6V-400Ah
Batteries number	4
Battery Pack	24 VDC- 9.6k Wh
xpected battery cycle	500 - 80%DOD
istribution Panel	
x 32A 1Ph 230V EEC plug for battery cl	narging
4x 230V outlet socket	
4x 16A USB outlet sockett	



