## designed and created for your needs

PORTABLE
SILENCED LINE
GASOLINE

## **power** and innovation

MGTP 6 AE

MGTP 7 AE 3F

MGTP 11 AE

MGTP 12 AE 3F

Designed to provide an exceptional level of performance for every work on site ensuring the right balance between power and ease of use





more sustainable and environmentally friendly future





## **HONDA**







AIR COOLED ENGINE **3000 r.p.m.** 









Code	PP77-6MS0	PP78-7TS0
On board control panel equipped with:	- DSE ON/OFF switch - DSE 3110 module will display warnings, shutdowns & engine status information as high temperature, low oil pressure, low fuel level warning, Volts & Frequency, running hrs, battery voltage monitoring - Circuit breaker - Emergency Stop - Soundproof canopy - Exhaust gas silencer - 2x32A 1ph 230V EEC socket - 1x16A 1ph 230V EEC socket	- DSE ON/OFF switch - DSE 3110 module will display warnings, shutdowns & engine status information as high temperature, low oil pressure, low fuel level warning, Volts & Frequency, running hrs, battery voltage monitoring - Circuit breaker - Emergency Stop - Soundproof canopy - Exhaust gas silencer - 1x 16A 3Ph 400V EEC socket - 1x 32A 1Ph 230V EEC socket
Generator		
Туре	Linz E1C10 M H	Linz E1S10M H
Power	6 kVA 230V	7 kVA 400V
Frequency	50 Hz	50 Hz
Engine		
Engine type	HONDA GX390	HONDA GX390
N° cylinders	1	1
Power	11 HP	11 HP
Engine speed	3000 r.p.m.	3000 r.p.m.
Cooling	Air	Air
Fuel	Unleaded gasoline	Unleaded gasoline
Starting system	Electric	Electric
Technical Data		
Fuel tank capacity (I)	21	21
Running Time (h)	7	7
Dimensions		
Dimensions (LxWxH) mm	970 x 600 x 750	970 x 600 x 750
Dry weight (kg)	190	190
Options	Trolley	Trolley



## PORTABLE SILENCED LINE











AIR COOLED ENGINE **3000 r.p.m.** 











Code	PP79-11MS0	PP80-12TS0
On board control panel equipped with:	- DSE ON/OFF switch - DSE 3110 module will display warnings, shutdowns & engine status information as high temperature, low oil pressure, low fuel level warning, Volts & Frequency, running hrs, battery voltage monitoring - Circuit breaker - Emergency Stop - Soundproof canopy - Exhaust gas silencer - 2x32A 1ph 230V EEC socket - 1x16A 1ph 230V EEC socket	- DSE ON/OFF switch - DSE 3110 module will display warnings, shutdowns & engine status information as high temperature, low oil pressure, low fuel level warning, Volts & Frequency, running hrs, battery voltage monitoring - Circuit breaker - Emergency Stop - Soundproof canopy - Exhaust gas silencer - 1x 16A 3Ph 400V EEC socket - 1x 32A 1Ph 230V EEC socket
Generator		
Туре	Linz E1C11M B	Linz E1S11M AS
Power	11 kVA 230V	12 kVA 400V
Frequency	50 Hz	50 Hz
Engine		
Engine type	HONDA GX630	HONDA GX630
N° cylinders	2	2
Power	20,8 HP	20,8 HP
Engine speed	3000 r.p.m.	3000 r.p.m.
Cooling	Air	Air
Fuel	Unleaded gasoline	Unleaded gasoline
Starting system	Electric	Electric
Technical Data		
Fuel tank capacity (I)	21	21
Running Time (h)	4,4	4,4
Dimensions		
Dimensions (LxWxH) mm	970 x 600 x 750	970 x 600 x 750
Dry weight (kg)	204	204
Bry Weight (hig)	204	201



