## designed and creater for your needs

Designed to provide an exceptional level of performance for every work on site ensuring the right balance between power and ease of use

X-SOLAR

4x100W LED - 8M

T-ZEROPRO

more sustainable and environmentally friendly future



www.trime.it

**Lighting Towers** 







LED TECHNOLOGY

## 3000 Sqm Illuminated area







## **APPLICATIONS**









## **FEATURES**

- Multi-directionally adjustable and tiltable floodlights
- Galvanized metalworks
- Forklift pockets for effective handling
- Plug & play, colour coded cables and connectors
- Guided main coiled cable to avoid damage during tower operation
- Swivel Central Lifting Eye with patent pending
- Certified wind stability up tp 80 km/h
- On board levels for guidance during stabilization
- No. 8 batteries AGM, Battery Pack 24Vdc 800Ah
- EU Homologated Road-tow trailer
- VICTRON controller for Tracking and Telematics e remote management





Dimensions & weight	
Dimensions min (mm)	3360x2138x2522 (LxWxH)
Dimensions max(mm)	3360x4150x8000 (LxWxH)
Total weight (kg)	1500
Floodlights	
Туре	Led
Power(each)	100W
Floodlights number	4
IP level	65
Illuminated area (sqm)	3000
Mast	
Lifting method	Hydraulic
Max Height	8 m
Max Wind Speed	80 km/h
Rotation	340°
Batteries	
Туре	AGM
Batteries number	8
Power Battery pack	24 Vdc 800 Ah
Expected battery cycle	500
Solar panel	
Power(each)	4x400W
Solar panel deployment	manual
Solar charge control	MPPT 150/60



